Hummerbee 500 Series Compact Loaders

525 Specifications:

Engine:	Kubota V1505 Diesel, 1.5L 4-Cylinder, Tier 4
Horsepower:	24.8 hp @ 2,600 RPM
Torque:	68.3 Ft-Lbs @ 1,700 RPM
4WD Transmission:	Single Speed
Maximum Speed:	10 mph
Standard Tires:	26x12.50x12; Ag/Pneumatic
Maximum Lift Height:	102" (to Hinge)
Maximum Lift Capacity:	2,000 lbs.: 2,700 lbs. w/Cntrwts.
Aux. Hydraulics Flow:	14 GPM
Total Weight:	4,510 lbs. w/Ag Tires; Pneumatic
Overall Height:	89.5" (Approx.)
Overall Length:	113" w/o Bucket
Overall Width:	55" w/Standard Tires
Fuel Capacity:	15 gal Tank
Hydraulic Oil Capacity:	15 gal Tank
Turning Radius:	42 Inches
Frame Oscillation:	+/-8 Degrees
Wheel Base:	53"
Ground Clearance:	7" from Ground to Transfer Case
FEATURES:	
Premium Kubota V1505 E	ngine
High Torque, Single Speed	d Transmission
Mechanical Joystick - Hy	draulic
Eaton Gear Pump	
14 GPM Hydraulics - Singl	e Remote
Rexroth Ground Drive	
Dana Axles	

Available: Fall 2024

525R Specifications:

Engine:	Kubota V1505 Diesel, 1.5L 4-Cylinder, Tier 4
Horsepower:	24.8 hp @ 2,600 RPM
Torque:	68.3 Ft-Lbs @ 1,700 RPM
4WD Transmission:	2-Speed
Maximum Speed:	12 mph/High; 5 mph/Low
Standard Tires:	26x12.50x12; Ag/Pneumatic
Maximum Lift Height:	102" (to Hinge)
Maximum Lift Capacity:	2,000 lbs.: 2,700 lbs. w/Cntrwts.
Aux. Hydraulics Flow:	14 GPM
Total Weight:	4,570 lbs. w/Ag Tires; Pneumatic
Overall Height:	89.5" (Approx.)
Overall Length:	113" w/o Bucket
Overall Width:	55" w/Standard Tires
Fuel Capacity:	15 gal Tank
Hydraulic Oil Capacity:	15 gal Tank
Turning Radius:	42 Inches
Frame Oscillation:	+/-8 Degrees
Wheel Base:	53"
Ground Clearance:	7" from Ground to Transfer Case
FEATURES:	
Premium Kubota V1505 Engine	
2-Speed, Dynamic Drive Shift On-The-Fly Transmission	
Piloted Joystick - 1 Electric Remote	
Eaton Gear Pump	
14 GPM Hydraulics	
Rexroth Ground Drive	
Dana Axles	

Available: Fall 2024

550GR Specifications:

Engine:	Kubota WG1605	
	Gasoline Powered	
Horsepower:	49 hp	
Torque:	88.51 Ft-Lbs @ 2,500 RPM	
4WD Transmission:	2-Speed	
Maximum Speed:	12 mph/High; 5 mph/Low	
Standard Tires:	29x12.50x12; Ag/Pneumatic	
Maximum Lift Height:	104" (to Hinge)	
Maximum Lift Capacity:	2,000 lbs.: 2,700 lbs. w/Cntrwts.	
Aux. Hydraulics Flow:	14 GPM	
Total Weight:	4,510 lbs. w/Ag Tires; Pneumatic	
Overall Height:	91" (Approx.)	
Overall Length:	113" w/o Bucket	
Overall Width:	55" w/Standard Tires	
Fuel Capacity:	15 gal Tank	
Hydraulic Oil Capacity:	15 gal Tank	
Turning Radius:	42 Inches	
Frame Oscillation:	+/-8 Degrees	
Wheel Base:	53"	
Ground Clearance:	8.5" from Ground to Transfer Case	
FEATURES: Same Features as the 525R, Plus:		
Kubota WG1605 / Liquid Cooled Gasoline Engine		
Same Durablility as a Diesel Engine		
Quieter than a Diesel Engine		
Piloted Joystick - Optional 2 Electric Remotes		
88.51 ft. lbs. Torque @ 2,9	500 RPM	
Best Value of any 49H	P Loader!	

Available: Fall 2024



REV. 09/11/24