



ArborPro

Tree Care Package



You Asked For It, You Got It.

While some compact loader manufacturers take a one-size-fits-all approach to their equipment offerings, Hummerbee RTE does things different. We listen to our customers, and build equipment for the way they work. That's why we tailor-made the ArborPro Tree Care Package specifically for the professional arborist—it's what you asked for.

Carefully designed and developed, this tool and accessory package is equipped to make your job easier and more productive—with good looks to boot! Available on all 500 Series Loaders, you can choose the ArborPro Appearance Package with custom paint and graphics or outfit any standard spec loader with the add-ons of your choice.



Chainsaw Holder



Rigging Bollard



Rear Tie-down D-Rings



Wheel-Mounted Tie-downs



Warning Beacon



Steel Toolbox



Liquid-filled Turf Tires



2 - 90 Lb. Counterweights

Upgrade any 500 Series Loader to an ArborPro!

ArborPro Package Includes:

Chainsaw Holder; Rigging Bollard; Wheel Tie-down Anchors; Liquid-filled Turf Tires; Rear Tie-down D-Rings; 2 - 90 Lb. Counterweights; Roof-mounted Warning Beacon; Steel Toolbox; Appearance Package: (Reseda Green and Black Paint Scheme with Pure Green (525M), Red (525R) or Sky Blue (550GR) Bolt-on Options; ArborPro Badging; Gator Graphic Decals).



	525M	525R	550GR
TECHNICAL DATA			
Engine:	Kubota V1505, Diesel, 1.5L, 4-Cyl.	Kubota V1505, Diesel, 1.5L, 4-Cyl.	Kubota WG1605, Gasoline Powered
Horsepower:	25 HP @ 2,600 RPM	25 HP @ 2,600 RPM	50 HP @ 2,600 RPM
Torque:	68.5 Ft-Lbs @ 1,700 RPM	68.5 Ft-Lbs @ 1,700 RPM	88.51 Ft-Lbs @ 2,500 RPM
Drivetrain:	4-Wheel Drive / Limited Slip	4-Wheel Drive / Limited Slip	4-Wheel Drive / Limited Slip
Transmission:	Single-Speed / Hydrostatic	2-Speed / Hydrostatic	2-Speed / Hydrostatic
Maximum Speed:	7 MPH	10 MPH/High; 4 MPH/Low	10 MPH/High; 4 MPH/Low
Fuel Capacity:	15 Gallons	15 Gallons	15 Gallons
Hydraulic Oil Capacity:	13 Gallons (Max)	13 Gallons (Max)	13 Gallons (Max)
Operator Controls:	Mechanical Valve Levers	Electronic Joystick	Electronic Joystick
Auxiliary Hydraulics Flow:	13 GPM / 3,000 PSI	13 GPM / 3,000 PSI	15 GPM / 3,000 PSI
Auxiliary Hydraulics Circuit:	2-Line	2-Line (4-Line Optional)	2-Line (4-Line Optional)
Operating Weight:	4,510 lbs. w/Pneumatic Ag Tires	4,570 lbs. w/Pneumatic Ag Tires	4,510 lbs. w/Pneumatic Ag Tires
Tipping Load with Counterweight with Arm Extended Horizontally:	At Tool Carrier 12" Load Center 3,900 lbs. 2,800 lbs.	At Tool Carrier 12" Load Center 3,900 lbs. 2,800 lbs.	At Tool Carrier 12" Load Center 3,900 lbs. 2,800 lbs.
Tipping Load w/o Counterweight with Arm Extended Horizontally:	At Tool Carrier 12" Load Center 3,400 lbs. 2,500 lbs.	At Tool Carrier 12" Load Center 3,400 lbs. 2,500 lbs.	At Tool Carrier 12" Load Center 3,400 lbs. 2,500 lbs.
DIMENSIONS			
Lift Height:	102" (to Hinge Pin)	102" (to Hinge Pin)	104" (to Hinge Pin)
Overall Length:	113" without Attachment	113" without Attachment	113" without Attachment
Overall Height:	89.5" (Approx.)	89.5" (Approx.)	91" (Approx.)
Overall Width:	55" with Standard Tires	55" with Standard Tires	55" with Standard Tires
Wheel Base:	53"	53"	53"
Standard Tires:	26x12x12; Liquid-filled Ag Tires	26x12x12; Liquid-filled Ag Tires	29x12.5x15; Liquid-filled Ag Tires
Ground Clearance:	7" (to Transfer Case)	7" (to Transfer Case)	8.5" (to Transfer Case)
Turning Radius:	42"	42"	42"
Frame Oscillation:	8 Degrees	8 Degrees	8 Degrees
ArborPro Package Paint Scheme:	Reseda Green/Black/Bright Green	Reseda Green/Black/Bright Red	Reseda Green/Black/Bright Blue

(800) 943-8677

www.hummerbee.com | info@hummerbee.com
200 Quicksilver Lane | Edmore, MI | 48829