



The World's Most Configurable All-Terrain Utility Forklifts!



25HP
Classic
4-Cylinder
Kubota Diesel

56HP
Turbo II
3-Cylinder
Kohler Diesel

74HP
XRT
4-Cylinder
Kohler Diesel



Built for the Way YOU Work!

Hummerbee forklifts are designed and engineered with the most configurable platforms of any compact rough terrain forklift in the world.



Made in the USA clearly has an advantage when you need a specialized utility forklift, tailor-made for your unique applications. Whatever industry you're in, Hummerbee forklifts can be equipped with multiple variations of hydraulics, attachments, controls, lights, tires, gauges, drives, ROPS/FOPS, and even masts, to meet your specific work requirements. That next level of customization and flexibility sets Hummerbee apart from everyone else. *Specialty is our business.*

Next Level Stuff...



OPTIONAL SSQA ADAPTER

Expand your capabilities by running any full-size skid steer attachment with a Hummerbee forklift! Simply attach the adapter to the fork carriage, grab your tool of choice, and you're on to the next task. There's no end to the possibilities!



AUXILIARY HYDRAULICS

With the option to add auxiliary hydraulics, you can maximize your Hummerbee's versatility! Quickly switch from one hydraulic tool to another, minimizing downtime, and eliminating the need for multiple types of outdoor equipment.



MULTI-FUNCTION JOYSTICK

If you prefer operating a joystick versus levers, we got you covered! Our ergonomic, easy-to-use, joystick provides quick, precise response to every command. And just to be sure it meets your needs, it's available with up to 6 button configurations.



2-SPEED TRANSMISSION

Standard on 2 models, our exclusive 2-Speed, Dynamic Drive, Rexroth® ground-drive transmission provides smooth, on-the-fly shifting while offering considerable low-end torque. Increase productivity and virtually cut your cycle time in half?

One Machine. Endless Possibilities.



Hummerbee Forklift Specifications

	<i>Classic</i>	<i>Turbo II</i>	<i>XRT</i>
TECHNICAL DATA			
Engine:	Kubota V1505, Diesel, 1.5L, 4-Cyl.	Kohler-KOI 1903TCR, 3-Cyl., Turbo	Kohler-KOI 2504TCR, 4-Cyl., Turbo
Horsepower:	25 HP @ 2,600 RPM	56 HP @ 2,600 RPM	74 HP @ 2,600 RPM
Torque:	68.5 Ft-Lbs @ 1,700 RPM	166 Ft-Lbs @ 1,500 RPM	221 Ft-Lbs @ 1,500 RPM
Maximum Lift Capacity:	1,600 lbs. / 2,000 lbs. w/Cntrwt.	2,000 lbs. / 3,000 lbs. w/Cntrwt.	3,000 lbs. / 4,000 lbs. w/Cntrwt.
Pick & Carry Capacity:	3,000 lbs. w/Cntrwt.	3,300 lbs. w/Cntrwt.	3,500 lbs. w/Cntrwt.
Operating Weight:	4,860 lbs. w/Liquid Filled Tires	5,660 lbs. w/Liquid-filled Tires	6,300 lbs. w/Liquid-filled Tires
Drive-train:	4-Wheel Drive / Limited Slip	4-Wheel Drive / Limited Slip	4-Wheel Drive / Limited Slip
Hydrostatic Transmission:	Single-Speed / 2-Speed Optional	2-Speed / Shift-On-The Fly	2-Speed / Shift-On-The Fly
Maximum Speed:	8 MPH / 11 MPH-High; 5 MPH-Low	12 MPH-High; 6 MPH-Low	12 MPH-High; 6 MPH-Low
Standard Tires:	29x12.5x15 / Liquid-filled Ag Tires	29x12.5x15 / Liquid-filled Ag Tires	29x12.5x15; Liquid-filled Ag Tires
Operator Controls:	Mechanical / Joystick Optional	Piloted Joystick	Piloted Joystick
Fuel Capacity:	15 Gallons	17 Gallons	12 Gallons
Hydraulic Oil Capacity:	13 Gallons (Max)	15 Gallons (Max)	10 Gallons (Max)
Auxiliary Hydraulics Flow:	13 GPM (Optional Configurations)	13 GPM (Optional Configurations)	13 GPM (Optional Configurations)
Hydraulic Steering:	5 GPM	5 GPM	5 GPM
Standard Color:	Yellow	Yellow	Yellow
DIMENSIONS			
Maximum Mast Height:	126" Standard / 144" Optional	126" Standard / 144" Optional	126" Standard / 144" Optional
Mast Tilt:	16 Degrees	16 Degrees	16 Degrees
Mast Side Shift:	6"	6"	6"
Fork Length:	42" Standard / 48" Optional	42" Standard / 48" Optional	42" Standard / 48" Optional
Overall Length:	97" / 140.5" w/42" Forks	95" / 138.5" w/42" Forks	108.3" / 151.8" w/42" Forks
Overall Height:	89" / 99" w/Optional 144" Mast	94.5" / 104.5" w/Optional 144" Mast	94" / 104" w/Optional 144" Mast
Overall Width:	55" with Standard Tires	55" with Standard Tires	55.5" with Standard Tires
Wheel Base:	47.5"	53.75"	49"
Ground Clearance:	8" (to Transfer Case)	7" (to Transfer Case)	9" (to Transfer Case)
Turning Radius:	44" - Inside / 99" - Outside	51" - Inside / 106" - Outside	49" - Inside / 104" - Outside
CONTACT YOUR HUMMERBEE SALES REPRESENTATIVE FOR MORE INFORMATION.			

As Shown on Front - Hummerbee Classic Equipped with:

- Multi-function Nursery Jaw Forks
- Skid Steer Quick-Attach Adapter
- Lightweight, Removable Canopy
- 13 GPM Aux. Hydraulics
- 84" Nursery Mast
- Folding ROPS



(800) 943-8677

www.hummerbee.com | info@hummerbee.com

200 Quicksilver Lane | Edmore, MI | 48829



REV. 03/2026